



Accesorios
 Acessórios
 Accessoires
 Accessories



Paso de tensión entre todos los conectores.

Passagem de tensão entre todos os conectores.

Passage de tension entre tous les connecteurs.

Passage of voltage between all the connectors.

Características técnicas	Características técnicas	Spécifications techniques	Technical specifications				
Referencia	Referência	Référence	Reference	5435	5436	5437	5438
Margen freq.	Margem freq.	Marge fréq.	Freq. range	5 - 2400 MHz			
Atenuación	IN - OUT (dB)		5 - 47 MHz	3,5	6,5	8	9,5
Atenuação			47 - 862 MHz	4,5	7	7,5	8,5
Atténuation			950 - 2400 MHz	5,5	9	9,5	9,5 ... 12
Atenuación	IN - OUT3 (dB)		5 - 47 MHz	—	6,5	—	10
Atenuação			47 - 862 MHz	—	6,5	—	9,5
Atténuation			950 - 2400 MHz	—	7	—	9
Rechazo entre salidas	(dB)		5 - 862 MHz	> 15	> 15	> 17	> 15
Rejeição entre saídas			950 - 2400 MHz	> 15	> 15	> 15	> 15
Réject entre sorties							
Rejection between outputs							
Tensión máx.	Tensão max.	Voltage max.	Max. voltage	40 V			
Corriente máx.	Corrente max.	Courant max.	Max. current	300 mA			

Televés

SMATV

Repartidores EMC
 Repartidores EMC
 Répartiteurs EMC
 Splitters EMC

Refs. 5435, 5436, 5437, 5438

8 mm max. $\varnothing \geq 6,5$ mm

8 mm max. $\varnothing \leq 6,5$ mm

Andaje de brida para facilitar el conexionado
 Encaixe da braçadeira para facilitar a ligação
 Fixation de la bride pour simplifier la connexion
 Cable clamp joint for easy connection.

Mismo pelado para cables de una misma brida.
 Mesmo descarnado para cabos da mesma braçadeira
 Même decoupe du câble par bride
 Same stripping for cables with the same clamp.

Aplicación

Aplicação

Application

Application

